

DYNAMIC INTERIOR MATT

RICH MATT EMULSION WITH ANTI-MOULD

Product Name	DYNAMIC INTERIOR MATT
Product Description	Dynamic Interior Matt is a special formulated with anti-mould properties to prevent mould growth on the interior wall and ceiling. It is durable emulsion with smooth matt finish, does not contain lead, mercury and heavy metals. Ideally suited for masonry surface for wall and ceiling, such as cement plastered walls, fibre ceiling boards in bathrooms, kitchens, bedroom, offices and residential buildings that creates a lively space and environment.
Designed Use	For use on new or previously painted interior surfaces such as brickwork, plaster, cement rendering and asbestos where an economical
Binder Type	Vinyl acrylic copolymer
Performance	<ul style="list-style-type: none"> • With anti-mould properties • Extra whiteness • Superior after dry hiding properties • Non-toxic, does not contain any lead, mercury and heavy metals • Environmental friendly product with low VOC and odour
Physical Properties Coverage* Volume Solids Dry Film Thickness	10 – 12 m ² /Lt @ 25 microns 37% 25 - 30 microns / coat (based on substrate condition)
Finishing Colours Finishing Pack Size	Refer to Kansai Paint's colour card Smooth matt 20 litres
Application Drying Times Dilution Cleaning Up	Surface dry : 20 mins ; Recoat : 1 – 2 hours <i>*Depend on temperature and humidity</i> Clean household water Clean household water
Dilution Ratio Brush or Roller Conventional Spray Airless Spray	Ready for use. If dilution is required, add up to 5% clean water. Dilution up to 10% clean water. Ready for use.
Spray Equipment Guide Conventional Spray Airless Spray	A typical set up would be a minimum atomising pressure of 2.8 kg/cm ² and fluid pressure of 0.4 kg/cm ³ with a nozzle size of 0.43 mm. A typical set up would be a minimum of 155 kg/cm ³ with nozzle size of 0.38 - 0.43 mm and a spray tip angle of 65°.
Surface Preparation	<p>Newly plastered surfaces : Interior walls & ceilings For new surfaces, allow surfaces to cure and dry out completely. Avoid painting when the moisture content is above 15% on a protimeter and alkalinity of the wall is still high above pH-9 or premature paint failure will occur. Large cracks must be appropriate fillers. Remove all loosely adhering residues by thoroughly brushing.</p> <p>Repainting : Interior walls & ceilings Check for powdery or chalk. These surface contaminants must be completely removed by washing with warm water and detergent solutions. Rinse with clean water, taking care to change the rinsing water regularly. If after</p>

thorough preparation the surface is still slightly powdery, it may be necessary to seal it with PAR Plasterseal solvent base wall sealer. Dilute the sealer up to 20% and apply liberally to allow the sealer to fully penetrate the surface and form a barrier that seals up the chalk.

Recommended Paint System
Newly plastered surfaces : Interior walls & ceilings

1 st		2 nd & 3 rd	
PAR Primer Sealer	Recoat 1 - 2 hours	Dynamic Interior Matt	Recoat 1 - 2 hours

Repainting : Interior walls & ceilings

1 st		2 nd & 3 rd	
PAR Plasterseal	Recoat 4 - 5 hours	Dynamic Interior Matt	Recoat 1 - 2 hours

NB : PAR Primer Sealer and PAR Plasterseal work best on surfaces with a moisture content of below 15% and alkalinity below pH-9, otherwise premature paint failure may occur.

Safety & Health Information

- Ensure adequate lighting and ventilation during application and drying.
- This product does not contain added lead or mercury.
- When applying paints, it is advisable to wear eye protection.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Use soap and water to remove splashes from skin.
- Storage: Keep container closed and store in clean and dry conditions.
- Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Do not empty into drains or water courses.
- This product is not flammable. Keep out of reach of children.
- Safety Data Sheet (SDS) is available upon request.

For further information on Product Data, please contact :

Decorative Sales Department

Kansai Paint Asia Pacific Sdn. Bhd. (705919-w)

9-3A, 9-5, 9-6 & 9-7, Level 9, Port Tech Tower, Jalan Tiara 3/KU1, Bandar Baru Klang, Selangor Darul Ehsan, Malaysia.

Website : www.kansaimalaysia.com Tel : +603 3002 4001 Fax : +603 3002 4002

**Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film and thickness and the skill of applicator.*

The information in this technical data sheet is given to the best of our knowledge based on laboratory testing and practical experience and is provided as a general advice only. No guarantee of results is implied since the conditions of use are beyond our control. It is the responsibility of the users to ensure the suitability and proper usage of the product. We reserve the right to change the data without prior notice.